

AIRMAN®



GENUINE

**HIGH PURITY
COMPRESSOR OIL
Long Life HP**

(For AIRMAN compressor 0.7MPa to 2.4MPa)

20l Pail size | 200l Drum size

**RELIABLE
HIGH QUALITY
LONGER LIFETIME
SUPREME PERFORMANCE**

HOKUETSU INDUSTRIES CO., LTD.

Specification

Item	Unit	Compressor oil Long Life HP
Applicable model* ¹	-	AIRMAN Portable/Stationary Compressor
Applicable pressure* ¹	MPa	0.7 to 2.4
Oil changing time* ²	Hour	Engine type : every 1,000* ⁴ Motor type : every 6,000* ³
ISO VG	-	46
Density (15°C)	g/cm ³	0.849
Color (ASTM)	-	L0.5
Flash point (COC)	°C	266
Pour point	°C	-32.5
Kinematic viscosity (40°C)	mm ² /s	46.7
Kinematic viscosity (100°C)	mm ² /s	7.71
Viscosity index	-	133
Total acid number	mgKOH/g	0.05
Demulsibility (54°C)	min	10
Copper strip corrosion (100°C, 3H)	-	1
Rust-preventing characteristics (60°C, 24H, Distilled water)	-	No rust
Foaming (Sequence I)	ml	20-0

Above values are representative values for reference purpose only. It may differ from actual item.

*¹ Excluding certain type of models. Please check product specification.

*² Depending on models, ambient environment and running condition.

*³ For SASG19S (1.4MPa), oil changing time is every 3000 hours.

*⁴ For PDSJ750S (2.07MPa), PDSK900S (2.41MPa), oil changing time is every 500 hours.

GENUINE PARTS

For inquiries and quotation, please contact Airman distributors or authorized dealers:



Compressor oil



Air filter



Oil Separator



Oil filter

